



ELSHAMS MODELİ KOMPLE HARMAN MAKİNASI (İKİNCİ TEMİZLEME ÜNİTELİ VE BANTLI)
TRESHER MACHINE EL SHAMS COMPLETE (WITH SECOND CLEANING SYSTEM AND FEEDING ELEVATOR)
ELSHAMS MODELE TOUT BATTAGE MACHINE DEUX NETTOIEMENT LA UNITE ET LE RUBAN

TEKNİK ÖZELLİKLER TECHNICAL SPECIFICATIONS TECHNIQUE PARTICULARITE

TIPI	Type	Type	1400
TOPLAM GENİŞLİK	Overall Widht	Total Largeur	2130
TOPLAM UZUNLUK	Overal Lenght	Total Langueur	
YOL DURUMUNDA	In Road Position	Route Situation	4400 mm
İŞ DURUMUNDA	In Work Position	Action Situation	5400 mm
TOPLAM YÜKSEKLİK	Overall Height	Total Hauteur	2740 mm
TOPLAM AĞIRLIK	Total Weight	Total Lenteur	2150 Kg
BATÖR TİPİ	Drum (Cylinder) Type	Batteuse Type	Parmaklı / Pegged (toothed) / Ladoigt
BATÖR ÇAPI	Drum Diameter	Diamètre de la batteuse	∅ 760 mm
PARMAK SIRA SAYISI	Number of Pegs Rows	Doight range la somme	6
PARMAK SAYISI	Number of Pegs	Doight la somme	460
KONTRBATÖR TİPİ	Concave Types	Contrbataur type	Yuvarlak Delikli / Round Holed / Rond Perfore
KONTRBATÖR DELİK ÇAPLARI	Diameter of Concave Holes	Contrbataur Perfore Diamètre	
MERCİMEK, K. MERCİMEK	Green and Red Lentiles	Lentille,Rouge Lentille	∅ 10 mm
ARPA, BUĞDAY, NOHUT	Whet, Barley, Chickpea	Orge, Blè, Pois Chiche	∅ 15 mm
FASULYE, BAKLA	Bean, Broad Bean	Haricot, Fève	∅ 20 mm
TAŞIMA DÜZENİ	Carrying System	Transport Ordre	Tek Dingil / Single Axled / Un Axe
LASTİKLER	Tyre Size	Pneus	750 X 16